## The Conesus!







## **COLORS**\*

## Cabinet



Brown Charcoal



Shell

Black Polyester

Cover

## **SPECS**

Seating Capacity	3 Seats
Dimensions	5'6" x 7' x 34" / 168 cm x 213 cm x 86 cm
Water Capacity	220 gallons / 850 liters
Weight	585 lbs. / 265 kg dry; 2,945 lbs. / 1,355 kg filled**
Jets	32 Total
Water Feature	N/A
Jet Pump 1	Two-Speed 1.5 HP, continuous duty 3.2 HP, breakdown torque
Jet Pump 2	N/A
Water Care System	Ozone System
Control System	LCD control panel 115 V / 15 amp,
	60 Hz convertible to 230 V / 50 amp Includes 15amp G.F.C.I. protected power cord
Lighting	•
Lighting Heater	Includes 15amp G.F.C.I. protected power cord
	Includes 15amp G.F.C.I. protected power cord  12 multi-color LED points of light
Heater	Includes 15amp G.F.C.I. protected power cord  12 multi-color LED points of light  Hi-Flow Heater 1000 W / 110 V, 4000 W / 230 V  FiberCor Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy
Heater Energy Efficiency	Includes 15amp G.F.C.I. protected power cord  12 multi-color LED points of light  Hi-Flow Heater 1000 W / 110 V, 4000 W / 230 V  FiberCor Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
Heater Energy Efficiency Effective Filtration Area	Includes 15amp G.F.C.I. protected power cord  12 multi-color LED points of light  Hi-Flow Heater 1000 W / 110 V, 4000 W / 230 V  FiberCor Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas  50 sq. ft., top loading filter
Heater Energy Efficiency  Effective Filtration Area Cover	Includes 15amp G.F.C.I. protected power cord  12 multi-color LED points of light  Hi-Flow Heater 1000 W / 110 V, 4000 W / 230 V  FiberCor Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas  50 sq. ft., top loading filter  Included

